

# Boxer Series

## SLIDING GATE OPENERS

### Boxer 500

Low-Voltage 24Vdc special designed provides easy installation and safety usage. UV stabilized cover on main structure gives great resistance to outdoor environment.

Stylish design create elegant appearance for great fit in home surroundings. Key protected release device for power failure operation.

#### SPEC \ Type

#### Boxer 500

|                         |                   |
|-------------------------|-------------------|
| Type Of Worm Gear       | Plastic           |
| Nominal Thrust          | 5000N             |
| Engine RPM              | 3800RPM           |
| Absorbed Power          | 144W              |
| Power Supply            | 24 Vdc            |
| Nominal Input Power     | 6A                |
| Gate Weight             | Up to 500 KG      |
| Gate Length             | 6M                |
| Max . Operating Current | 5.5A for max. 10s |
| Operating Temperature   | -20°C~+50°C       |
| Dimension               | 250 x 170 x 275mm |
| Speed                   | 27.10 cm/s        |




# Boxer Series

## SLIDING GATE OPENERS



Quick Release Device



LED Display



Spring Limit Switch



Magnetic Limit Switch  
(Optional)

### Accessories



CB17

#### CB Series Control System

Smart control with intelligent functions

- Power input 110AV/230AV are available for optional
- Two back-up batteries support for power failure
- Build-in radio receiver for matching transmitters
- Over-current design for European safety regulation
- Elegant design and easy step installation
- Coordinate with CB16/CB20



#### PF2 Flashing Light

Flashing Light powered with 24Vdc

- Unique inner-shape design for maximum light efficiency
- Halogen bulb usage provide excellent illumination
- Vertical and Horizontal install are available



#### TM3 Transmitter

4-Channel Remote

- Four-channel transmitter with programed features
- Up to 50m transmitting distance
- With rolling code of 433MHz



#### H3 Photocell

Photocell of receiver/transmitter

- Safety device for up to 30m application
- Power input of AC/DC 12 ~ 24V
- Waterproof resistance design for outdoor environment



#### Nylon Rack

- Rack of 1m long and 2cm thick.